

OPEN TOPS

SUITABLE FOR THE CARRIAGE OF AWKWARD, INDIVISIBLE OR OVER-SIZED CARGO DESIGNED FOR LOADING THROUGH BOTH THE TOP AND REAR DOORS

FEATURES

- Corten steel construction
- Removable header rail at door opening
- High strength top rails with removable anti-theft roof bows
- Heavy duty TIR approved tarpaulin
- Heavy duty floor with truck load of floor strength test of 7,260 kgs
- Low tare weight
- Excellence in quality assurance and depot repair procedures
- Two locking bars fixed to each door
- Epoxy zinc rich primer applied to external and internal surfaces (excluding wooden floor)

ADVANTAGES

- Provides extra strength
- Unrestricted access through the door opening for abnormal loads
- Allows loading and unloading from above for abnormal loads
- Helps to protect the cargo
- High durability
- Additional payload
- Extends in-service life
- Increases cargo security
- Reduces corrosion
- Improves cosmetic appearance



TECHNICAL SPECIFICATIONS

WEIGHT	20'	40'
MAXIMUM GROSS WEIGHT	30,480 kgs	32,500 kgs
TARE WEIGHT	2,150 kgs	3,650 kgs
PAYLOAD	28,330 kgs	28,850 kgs
INTERNAL DIMENSIONS		
INTERNAL CUBIC CAPACITY	32.5 cu.m	66.4 cu.m
INTERNAL LENGTH	5,898 mm	12,032 mm
INTERNAL WIDTH	2,352 mm	2,352 mm
INTERNAL HEIGHT	2,348 mm	2,348 mm



T740/4/OPENTOPS/FEB 2022

GLOBAL EXPERTISE WITH LOCAL KNOWLEDGE. FOR DETAILED SPECIFICATIONS OF OUR PRODUCT OFFERING AND TO DISCUSS OUR FLEXIBLE LEASING SOLUTIONS, PLEASE CONTACT YOUR REGIONAL SEACO LEASING REPRESENTATIVE, VISIT: [SEACOGLOBAL.COM/CONTACT-US/CONTAINER-LEASING](https://seacoglobal.com/contact-us/container-leasing)

AFRICA

- (+27) 21 702 3631
- cs.southafrica@seacoglobal.com
- seacoglobal.co.za

AMERICAS

- (+1) 281 377 3200 ext. 2131
- cs.americas@seacoglobal.com

EUROPE

- (+49) 40 8080 3119
- cs.emeia@seacoglobal.com

INDIA/S.ASIA

- (+91) 22 6179 0644
- cs.isc@seacoglobal.com

REST OF ASIA

- (+65) 65 951 900
- cs.asiapacific@seacoglobal.com

OCEANIA

- (+61) 2 9290 1455
- cs.oceania@seacoglobal.com
- seacoglobal.com.au